

Community Development Department

Planning Division Building Safety Division Environmental Health Division

117 NW Lafayette Avenue Bend Oregon 97701-1925 (541)388-6575 FAX (541)385-1764 http://www.co.deschutes.or.us/cdd/

TANK ABANDONMENT PROCEDURES

\checkmark		
	ons The tank(s) contents must be pumped completely emopy of the pumper's receipt to this form.	npty by a licensed sewage disposal service.
□ Select OI	NE of the following 3 options:	
A. C	Removal Check with the local landfill or local recycler locations are approved to accept used septic tanks. Ma location was in use prior to requesting an inspection.	
В. □	<u>Fill in place</u> The top of the tank shall be removed before filling. Destroy steel or plastic tops and cave in concrete lids. Fill tanks with sand or bar-run gravel and pack the tank so as to eliminate void areas. For inspection; fill tanks to the tops of the vertical sides and request an inspection using the instructions below. After the inspection is completed, you will need to fill the tank to final grade.	
C. \sqsubset	C. <u>Crush and bury</u> After pumping the tank, crush the tank so that there are no void areas. Leave the crushed tank visible for the inspection.	
✓ ✓ ✓ You may t	Inspection To request an inspection, the following must Check the appropriate boxes above, fill out the location and permit # below, attach a copy of the receipt from the pumper, and sign and turn in this form. urn this information in to the Bend, Redmond, or La Pine the inspection will usually take place within the next 2 work.	location office. Once the information is
Septic Permit #	Contact Name:	Contact Phone #
Job Site Address_		City/State/Zip
	above information is true and complete to the best of my on the above stated lot has taken place in accordance with	
•	Contractor's Signature	
	Remember to attach a copy of the pumper's re	eceipt with this form.

Note: Components of the Decommissioned System

Drainfields can be left intact but they should not be excavated for a year after the last use. Distribution boxes should be pumped out by a licensed pumper and removed or filled in location. Sand Filter mounds can be left in place, but if removed, they should not be excavated for a year after the last use.